

WESTERN ELECTRICAL

HORTICULTURAL GROW LAMP

600W HPS DE PRO HV




DIMENSIONS (mm)	NOMINAL VALUE
D - Bulb Diameter	33
L - Bulb Length	325
MOL - Max Overall Length	395
Max Base to Bulb	3



- DELIVERS SUPERIOR PERFORMANCE FOR HORTICULTURAL APPLICATIONS
- THE PRO HV LINE IS ENGINEERED FOR PROFESSIONAL GROWERS
- BENCHMARK-SETTING PPF OUTPUT AND EFFICIENCY
- WORKS WITH ELECTRONIC ULTRA HIGH FREQUENCY 400V BALLASTS
- SUITS DOUBLE ENDED FIXTURES
- IDEAL FOR FLOWERING

SPECTRUM:



WESTERN ELECTRICAL

HORTICULTURAL GROW LAMP

600W HPS DE PRO HV

GENERAL CHARACTERISTICS

Cap-Base	DE
Bulb (Size & Material)	T33 - Quartz Glass, L=325mm
Bulb Finish	Clear
Arc Tube Material	PCA
Operating Position	Horizontal (H)
Max Bulb Temperature (°C)	400
Rated Averaged Life (h)	10,000
Dimmable	YES

PRODUCT DATA

Product Name	600W HPS HV DE Hydroponic Lamp
Manufacturer Code	HPS600 / H / T33 / DE / PRO HV
Lamps Per Carton	12
Certification Marks	CE

ELECTRICAL DATA

NOMINAL VALUE

Lamp Rated Wattage (W)	600
Lamp Operating Voltage (V)	205
Lamp Current (A)	3.4
Ignition Type	Pulse-Start
Ignition Voltage (kV)	4.5~5
Ignition Time (s)	5 MAX.
Run-up Time 90% (min)	7 MAX.
Typical Hot Restart Time (min)	8 MAX.
Reference Ballast Characteristics	240V-2.9A-50Hz

LIGHT PARAMETERS

NOMINAL VALUE

Color Rendering Index (%)	28
Color Temperature (K)	2,100
Luminous Flux (Lm)	95,000
Luminous Efficacy (Lm/w)	142
PPF (umol/s)	1,200
PPF Efficacy (umol/s/w)	1.79

TYPICAL PAR MAINTENANCE



TYPICAL LUMEN MAINTENANCE

